

COMPANY NAME	DATE
ADDRESS	PO#
	PHONE FAX
	CONTACT

SO#	TAKEN BY:
NO. OF DUPLICATE CONTROLLERS	
CONFIG#	
SERIAL NUMBERS:	

372-720-02-XXX-YYY

Top Bottom  
Configuration

TOP CHANNEL

1. Choose gas to be detected:
2. Choose full scale or range of PPM level desired: 0-50 special only \_\_\_\_\_
3. Is this controller connected to a Remote Cal or SafeCAL Module?  
If YES, go to step 3. If NO, choose desired concentration (ppm) to be used as Cal Gas.  
 PPM Go to step 4.
3. Is output from Detector Head 4-20mA or 1-5mA
4. Choose auxillary (recorder) output signal. 4-20mA 1-5V
5. For each Alarm choose (circle) desired configuration and setpoint values.
 

LO ALARM <input type="checkbox"/> PPM	HI ALARM <input type="checkbox"/> PPM	HIHI ALARM <input type="checkbox"/> PPM
Latching or NonLatching	Latching or NonLatching	Latching or NonLatching
Normally Energized or De-energized	Normally Energized or De-energized	Normally Energized or De-energized
Normally Open or Closed	Normally Open or Closed	Normally Open or Closed

1. Choose gas to be detected:
2. Choose full scale or range of PPM level desired: 0-50 special only \_\_\_\_\_
3. Is this controller connected to a Remote Cal or SafeCAL Module?  
If YES, goto step 3. If NO, choose desired concentration (ppm) to be used as Cal Gas.  
 PPM Go to step 4.
3. Is output from Detector Head 4-20mA or 1-5mA
4. Choose auxillary (recorder) output signal. 4-20mA 1-5V
5. For each Alarm choose (circle) desired configuration and setpoint values.
 

LO ALARM <input type="checkbox"/> PPM	HI ALARM <input type="checkbox"/> PPM	HIHI ALARM <input type="checkbox"/> PPM
Latching or NonLatching	Latching or NonLatching	Latching or NonLatching
Normally Energized or De-energized	Normally Energized or De-energized	Normally Energized or De-energized
Normally Open or Closed	Normally Open or Closed	Normally Open or Closed

BOTTOM CHANNEL

